

Page: 1/11

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

1 Identification

· Product identifier

· Trade name: Die-Slide Renovate: PDR 88

· Other means of identification: No other identifiers

· Recommended use and restriction on use

· Recommended use: Coating material

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Preco, Inc. 9705 Commerce Parkway Lenexa, KS 66219 913-541-0066

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:







GHS02 GHS07 GHS08

· Signal word: Danger

· Hazard statements:

H225 Highly flammable liquid and vapor.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist, vapors, or spray.

(Cont'd. on page 2)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

(Cont'd. of page 1)

Trade name: Die-Slide Renovate: PDR 88

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection. P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:		
108-21-4	isopropyl acetate Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	50-75%
64741-66-8	Naphtha (petroleum), light alkylate \$\infty\$ Asp. Tox. 1, H304	25-50%
64742-47-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	<10%

· Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- Description of first aid measures
- · After inhalation:

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

Seek medical help for symptoms or if unconscious.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Do not pull solidified product away from the skin.

Wash with soap and water.

(Cont'd. on page 3)



Page: 3/11

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Trade name: Die-Slide Renovate: PDR 88

(Cont'd. of page 2)

Revision: April 03, 2019

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Dizziness

Coughing

Irritating to eves.

Slight irritant effect on skin and mucous membranes.

· Danger:

May be fatal if swallowed and enters airways.

Danger of impaired breathing.

Indication of any immediate medical attention and special treatment needed:

If necessary oxygen respiration treatment.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Alcohol resistant foam

Carbon dioxide

Gaseous extinguishing agents

Fire-extinguishing powder

Water fog / haze

· For safety reasons unsuitable extinguishing agents:

Water stream.

Water spray

Special hazards arising from the substance or mixture

Highly flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Eliminate all ignition sources if safe to do so.

Cool endangered containers with water fog.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

(Cont'd. on page 4)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide Renovate: PDR 88

(Cont'd. of page 3)

- Environmental precautions Avoid release to the environment.
- · Methods and material for containment and cleaning up

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Allow to solidify. Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- Precautions for safe handling:

Use only in well ventilated areas.

Keep out of reach of children.

Open and handle receptacle with care.

Avoid contact with the eyes and skin.

Avoid breathing mist, vapors, or spray.

Information about protection against explosions and fires:

Highly flammable liquid and vapor.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Protect from humidity and water.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

PFL (LISA)

Components with limit values that require monitoring at the workplace

Long-term value: 950 mg/m³ 250 ppm

108-21-4 isopropyl acetate

. == (• • · ·)	= 0.19
TLV (USA)	Short-term value: 626 mg/m³, 150 ppm Long-term value: 417 mg/m³, 100 ppm
	Long-term value: 417 mg/m³, 100 ppm
FL (Canada)	Short-term value: 200 ppm

Long-term value: 100 ppm

Short-term value: 200 ppm

EV (Canada) Long-term value: 100 ppm

LMPE (Mexico) | Short-term value: 200 ppm

Long-term value: 100 ppm

(Cont'd. on page 5)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide Renovate: PDR 88

(Cont'd. of page 4)

64742-47-8 Distillates (petroleum), hydrotreated light

EL (Canada) Long-term value: 200 mg/m³

Skin

Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

Avoid breathing mist, vapors, or spray.

- Engineering controls: Provide adequate ventilation.
- Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:



Protective gloves

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

9 Physical and chemical properties

Information on basic physical a Appearance:	and chemical properties	
Form: Color: Odor: Odor threshold:	Liquid According to product specification Characteristic Not determined.	
· pH-value: · Melting point/Melting range: · Boiling point/Boiling range:	Not determined. Not determined. 92 °C (197.6 °F)	
· Flash point:	<15 °C (<59 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	

(Cont'd. on page 6)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide Renovate: PDR 88

	(Cont'd. of page 5)
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
Oxidizing properties:	Not determined.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	0.89
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with	
Water:	Slowly reacts with water.
Partition coefficient (n-octanol/water): Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Highly flammable liquid and vapor.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Reacts with oxidizing agents.

Reacts with peroxides.

Toxic fumes may be released if heated above the decomposition point.

- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

(Cont'd. on page 7)



Page: 7/11

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide Renovate: PDR 88

(Cont'd. of page 6)

LD/LC50 values that are relevant for classification:

108-21-4 isopropyl acetate

Oral LD50 3000 mg/kg (rat)

- · Primary irritant effect:
- On the skin: Based on available data, the classification criteria are not met.
- · On the eve: Irritating effect.
- · Sensitization: Based on available data, the classification criteria are not met.

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: May cause drowsiness or dizziness.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- · Toxicity
- · Aquatic toxicity Harmful to aquatic life with long lasting effects.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

Avoid release to the environment.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

· Waste treatment methods

(Cont'd. on page 8)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide Renovate: PDR 88

(Cont'd. of page 7)

· Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

Transport information		
UN-Number DOT, ADR/RID/ADN, IMDG, IATA	UN1139	
UN proper shipping name DOT, IATA ADR/RID/ADN, IMDG	Coating solution COATING SOLUTION	
Transport hazard class(es)		
DOT		
Name III		
Class	3	
Label	3 	
ADR/RID/ADN		
Class	3 (F1)	
Label	3	
IMDG, IATA		
Class	3	
Label	3	
Packing group DOT, ADR/RID/ADN, IMDG, IATA	II	
Environmental hazards Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

33

Revision: April 03, 2019

Trade name: Die-Slide Renovate: PDR 88

(Cont'd. of page 8)

· Danger code (Kemler):

· EMS Number: F-E,S-E

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

- · Transport/Additional information:
- · DOT



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· ADR/RID/ADN



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

·IMDG



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Subst	ances Cont	troi Act)
---------------------	------------	-----------

108-21-4	isopropyl acetate
64741-66-8	Naphtha (petroleum), light alkylate
64742-47-8	Distillates (petroleum), hydrotreated light
108419-34-7	acetic acid, C9-11-branched alkyl esters, C10-rich

(Cont'd. on page 10)



Page: 10/11

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Trade name: Die-Slide Renovate: PDR 88

(Cont'd. of page 9)

Revision: April 03, 2019

64742-16-1 Petroleum Hydrocarbon Resin

70131-67-8 Dimethyl siloxane, hydroxy-terminated

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL): (Substances not listed.)

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

(Cont'd. on page 11)





Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide Renovate: PDR 88

(Cont'd. of page 10)

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com