

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

1 Identification

[•] Product identifier

Trade name: Die-Slide: PDS 66

· Other means of identification: No other identifiers

· Recommended use and restriction on use

- · Recommended use: Coating material
- · Restrictions on use: No relevant information available.

[•] Details of the supplier of the Safety Data Sheet

• Manufacturer/Supplier: Preco, Inc. 9705 Commerce Parkway Lenexa, KS 66219 913-541-0066

· Emergency telephone number:

ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

[·] Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



Signal word: Danger
Hazard statements: H225 Highly flammable liquid and vapor. H302 Harmful if swallowed. H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways.
Precautionary statements:

(Cont'd. on page 2)





earment Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide: PDS 66

Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection.
If swallowed: Immediately call a poison center/doctor.
Rinse mouth.
Do NOT induce vomiting.
3 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
B IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use foam, powder, or carbon dioxide for extinction.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components		
64741-66-8	Naphtha (petroleum), light alkylate	40-60%
	🚯 Asp. Tox. 1, H304	
108-21-4	isopropyl acetate	20-30%
	 Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336 	
475645-84-2	cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine Flam. Liq. 2, H225 Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302	10-20%
64742-47-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	<10%
919-30-2	3-aminopropyltriethoxysilane	<1%
	(Cont'd	. on page 3)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

(Cont'd. of page 2)

Trade name: Die-Slide: PDS 66

Skin Corr. 1B, H314
 Acute Tox. 4, H302; Skin Sens. 1, H317

• Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

After inhalation:		
Supply fresh air.		
Provide oxygen treatm	ent if affected person has difficulty breathing.	
	symptoms or if unconscious.	
In case of unconscious	sness place patient stably in side position for transportation.	
After skin contact:		
	roduct away from the skin.	
Wash with soap and w		
If skin irritation or rash	occurs: Get medical advice/attention.	
After eye contact:		
Remove contact lense		
	several minutes under running water. Then consult a doctor.	
After swallowing:		
	hen drink plenty of water.	
	g; immediately call for medical help.	
	le lying on their back should be turned onto their side.	
	otoms and effects, both acute and delayed:	
Breathing difficulty		
Dizziness		
Coughing		
Irritant to skin and muc	cous memoranes.	
Eye damage.		
Allergic reactions		
Danger: Harmful if swallowed.		
Danger of impaired bre	oathing	
	ed and enters airways.	
	nediate medical attention and special treatment needed:	
	e of vomiting, danger of entering the lungs.	
If necessary oxygen re		
	pneumonia and pulmonary edema.	

5 Fire-fighting measures

[·] Extinguishing media

• Suitable extinguishing agents:

Alcohol resistant foam Carbon dioxide

Gaseous extinguishing agents

(Cont'd. on page 4)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide: PDS 66

(Cont'd. of page 3)

Fire-extinguishing powder
Water fog / haze
For safety reasons unsuitable extinguishing agents:
Water stream.
Water spray
Special hazards arising from the substance or mixture
Highly flammable liquid and vapor.
Formation of toxic gases is possible during heating or in case of fire.
Advice for firefighters
Protective equipment:
Wear self-contained respiratory protective device.
Wear fully protective suit.
Additional information:
Eliminate all ignition sources if safe to do so.
Cool endangered containers with water fog.

6 Accidental release measures

[•] Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions Avoid release to the environment.

Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

[·] Handling

Precautions for safe handling:

Use only in well ventilated areas.

Keep out of reach of children.

Open and handle receptacle with care.

Avoid contact with the eyes and skin.

Avoid breathing mist, vapors, or spray.

Information about protection against explosions and fires:

Highly flammable liquid and vapor.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

• Conditions for safe storage, including any incompatibilities

$^{\rm \cdot}$ Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

(Cont'd. on page 5)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide: PDS 66

(Cont'd. of page 4)

Protect from humidity and water.

Information about storage in one common storage facility: Store away from foodstuffs.

Store away from oxidizing agents.

Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

[·] Control parameters

Components with limit values that require monitoring at the workplace:		
108-21-4 isopropyl acetate		
PEL (USA)	Long-term value: 950 mg/m ³ , 250 ppm	
TLV (USA)	Short-term value: 626 mg/m³, 150 ppm Long-term value: 417 mg/m³, 100 ppm	
EL (Canada)	Short-term value: 200 ppm Long-term value: 100 ppm	
EV (Canada)	Short-term value: 200 ppm Long-term value: 100 ppm	
LMPE (Mexico)	Short-term value: 200 ppm Long-term value: 100 ppm	
64742-47-8 Distillates (petroleum), hydrotreated light		
EL (Canada)	Long-term value: 200 mg/m³ Skin	

• Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Engineering controls: Provide adequate ventilation.
- Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:



Protective gloves

Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear. • **Body protection:** Protective work clothing

• Limitation and supervision of exposure into the environment No relevant information available.

Risk management measures No relevant information available.





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide: PDS 66

(Cont'd. of page 5)

Physical and chemical properties		
Information on basic physical and chemical properties		
· Appearance:		
Form:	Liquid	
Color:	According to product specification	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
 Melting point/Melting range: 	Not determined.	
 Boiling point/Boiling range: 	104 °C (219.2 °F)	
· Flash point:	<15 °C (<59 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
 Oxidizing properties: 	Not determined.	
· Vapor pressure:	Not determined.	
· Density:		
Relative density:	0.8	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
 Solubility in / Miscibility with 		
Water:	Slowly reacts with water.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Other information	No relevant information available.	

10 Stability and reactivity

• **Reactivity:** No relevant information available.

- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- Possibility of hazardous reactions

Highly flammable liquid and vapor.

(Cont'd. on page 7)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide: PDS 66

(Cont'd. of page 6)

Used empty containers may contain product gases which form explosive mixtures with air. Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized. Reacts with oxidizing agents.

Reacts with peroxides.

Toxic fumes may be released if heated above the decomposition point.

• Conditions to avoid Excessive heat.

· Incompatible materials Oxidizers

[•] Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)

11 Toxicological information

[•] Information on toxicological effects

· Acute toxicity: Harmful if swallowed.

· LD/LC50 values that are relevant for classification:

475645-84-2 cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine

Oral LD50 >300-2000 mg/kg (rat)

919-30-2 3-aminopropyltriethoxysilane

Oral LD50 1780 mg/kg (rat)

Dermal LD50 4000 mg/kg (rabbit)

Primary irritant effect:

• On the skin: Irritant to skin and mucous membranes.

- On the eye: Strong irritant with the danger of severe eye injury.
- Sensitization: Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

• NTP (National Toxicology Program):

None of the ingredients are listed.

• OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

• Germ cell mutagenicity: Based on available data, the classification criteria are not met.

- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: May cause drowsiness or dizziness.

• STOT-repeated exposure: Based on available data, the classification criteria are not met.

 \cdot Aspiration hazard: May be fatal if swallowed and enters airways.





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide: PDS 66

(Cont'd. of page 7)

Toxic	•
•	tic toxicity
Harmf	ul to aquatic life with long lasting effects.
47564	5-84-2 cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine
LC50	57.1 mg/l (zebra fish)
Persi	stence and degradability No relevant information available.
Bioac	cumulative potential: No relevant information available.
Mobil	ity in soil: No relevant information available.
Addit	ional ecological information
Gener	ral notes:
	release to the environment.
	o available data on eliminability/decomposition and bioaccumulation potential prolonged terr
	ge of the environment can not be excluded.
	Its of PBT and vPvB assessment
	Not applicable.
	: Not applicable. r adverse effects No relevant information available.

13 Disposal considerations

[·] Waste treatment methods

· Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

[·] Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR/RID/ADN, IMDG, IATA	UN1139	
· UN proper shipping name		
· DOT, IATA	Coating solution	
· ADR/RID/ADN, IMDG	COATING SOLUTION	



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

ade name: Die-Slide: PDS 66	
	(Cont'd. of pag
DOT	
Class	3
Label ADR/RID/ADN	3
Class	3 (F1)
Label IMDG, IATA	3
Class Label	3 3
Packing group DOT, ADR/RID/ADN, IMDG, IATA	
Environmental hazards Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler): EMS Number:	33 F-E, <u>S-E</u>
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
 Transport/Additional information: DOT 	
\checkmark	nan 30 kg gross and inner packagings less than 5 L each.
ADR/RID/ADN	
Limited Quantity for packages less the	nan 30 kg gross and inner packagings less than 5 L each.
IMDG	
	(Cont'd. on page



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide: PDS 66

(Cont'd. of page 9)

Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture
 United States (USA)

· SARA

• Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

• TSCA (Toxic Substances Control Act)

64741-66-8 Naphtha (petroleum), light alkylate

108-21-4 isopropyl acetate

475645-84-2 cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine

64742-47-8 Distillates (petroleum), hydrotreated light

108419-34-7 acetic acid, C9-11-branched alkyl esters, C10-rich

64742-16-1 Petroleum Hydrocarbon Resin

919-30-2 3-aminopropyltriethoxysilane

70131-67-8 Dimethyl siloxane, hydroxy-terminated

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

• Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

(Cont'd. on page 11)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 03, 2019

Trade name: Die-Slide: PDS 66

(Cont'd. of page 10)

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL): (Substances not listed.)

All ingredients listed on DSL or NDSL.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com